



Best/Flex Roller

Gravity Applications

Excellent for handling odd shaped boxes, bags and low grade corrugated cartons that could get hung up on skatewheel conveyors.

Move in and out of trucks with POWERTRAX for faster, safer, easier loading and unloading. See back cover.

- 150 lbs. capacity per linear ft.
- 1³/₈" rollers
- 30" to 42¹/₂" adjustable conveyor height
- 18", 24" and 30" conveyor widths
- Available in any length to fit your applications

The above conveyor is equipped with an optional package stop that folds out of the way when not needed.

1-800-327-9209

www.bestconveyors.com

SPECIFICATIONS

	Model Number	Standard Lengths Compacted to Expanded	Leg Sets Per Unit	Roller Axle Centers EXTENDED	Approx. Shipping Weight
16" WIDTHS	B/FR-18-12	4' to 12'	4	5"	225 lbs.
	B/FR-18-16	5'4" to 16'	5	5"	290 lbs.
	B/FR-18-20	6'8" to 20'	6	5"	360 lbs.
	B/FR-18-24	8' to 24'	7	5"	425 lbs.
24" WIDTHS	B/FR-24-12	4' to 12'	4	5"	240 lbs.
	B/FR-24-16	5'4" to 16'	5	5"	305 lbs.
	B/FR-24-20	6'8" to 20'	6	5"	375 lbs.
	B/FR-24-24	8' to 24'	7	5"	440 lbs.
30" WIDTHS	B/FR-30-12	4' to 12'	4	5"	255 lbs.
	B/FR-30-16	5'4" to 16'	5	5"	320 lbs.
	B/FR-30-20	6'8" to 20'	6	5"	390 lbs.
	B/FR-30-24	8' to 24'	7	5"	455 lbs.

Adjustable Height: Standard adjustable range is from 30" to 42 1/2". 6 inch caster option adds 1 1/2" to conveyor height to make adjustable range from 31 1/2" to 44". 8 inch caster option adds 3 1/2" to conveyor height to make adjustable range from 33 1/2" to 46".

Axle Centers: When expanded, the distance between axle centers is 5". Optional 3" and 4" axle centers are available. Optional axle centers affect compacted conveyor length. Call our Sales Team for assistance.

Extended Lengths: BEST/FLEX Gravity Roller conveyors are available in any length. If your application requires a length not listed in the above chart, call our Sales Team for assistance.

PERFORMANCE OPTIONS



Package Stop.
Stops cartons at the end of the conveyor and folds down out of the way when not needed.



Side Rails.
Prevents cartons from skewing off the conveyor in accumulation applications.



Leg Connect Brackets.
Easily connects two or more conveyors to span greater distances.



Axle Centers.
Optional 3" and 4" axle centers are available for small package applications.



Colson 6" x 2" Swivel Casters.
For easier rolling over uneven surfaces. Adds 1 1/2" to the conveyor height.



Heavy Duty Option.
BEST/FLEX Roller conveyors are available with heavy duty 1.9" rollers. Call our Sales Team for assistance.

FEATURES

- **Self Tracking**—Cartons follow the twists and turns of the conveyor path without using engineered curves.
- **Adjustable Height**—Simply turn the locking knob to raise or lower the conveyor bed height.
- **Square Tubing Legs**—BEST was the first to offer heavy duty square tubing legs for longer service life.
- **1 1/2" Side Plates**—Aluminum alloy construction features a ribbed design for added durability. Assembled with bolts and lock nuts.
- **Casters with brakes**—Colson 5" x 1 1/4" swivel casters roll easily. Caster brakes lock both wheel and swivel simultaneously while the conveyor is in use.